



HISTORIC PRESERVATION COMMISSION

Marc Elrich
County Executive

Robert K. Sutton
Chairman

Date: December 11, 2023

MEMORANDUM

TO: Rabbiah Sabbakhan, DPS Director Department of
Permitting Services

FROM: Chris Berger
Historic Preservation Section
Maryland-National Capital Park & Planning Commission

SUBJECT: Historic Area Work Permit #1051671 - Solar Panels

The Montgomery County Historic Preservation Commission (HPC) has reviewed the attached application for a Historic Area Work Permit (HAWP). This application was **Approved** by the HPC Staff.

The HPC staff has reviewed and stamped the attached construction drawings.

THE BUILDING PERMIT FOR THIS PROJECT SHALL BE ISSUED CONDITIONAL UPON ADHERENCE TO THE ABOVE APPROVED HAWP CONDITIONS AND MAY REQUIRE APPROVAL BY DPS OR ANOTHER LOCAL OFFICE BEFORE WORK CAN BEGIN.

Applicant: Ryan Doyle
Address: 7317 Willow Avenue, Takoma Park

This HAWP approval is subject to the general condition that the applicant will obtain all other applicable Montgomery County or local government agency permits. After the issuance of these permits, the applicant must contact this Historic Preservation Office if any changes to the approved plan are made. Once work is complete the applicant will contact Chris Berger at 301-495-4571 or chris.berger@montgomeryplanning.org to schedule a follow-up site visit.





HISTORIC PRESERVATION COMMISSION

HAWP #: _____ at: _____

submitted on: _____

has been reviewed and determined that the proposal fits into the following category/categories:

Repair or replacement of a masonry foundation with new masonry materials that closely match the original in appearance;

Installation of vents or venting pipes in locations not visible from the public right-of-way;

New gutters and downspouts;

Removal of vinyl, aluminum, asbestos, or other artificial siding when the original siding is to be repaired and/or replaced in kind;

Removal of accessory buildings that are not original to the site or non-historic construction;

Repair or replacement of missing or deteriorated architectural details such as trim or other millwork, stairs or stoops, porch decking or ceilings, columns, railings, balusters, brackets shutters, etc., with new materials that match the old in design, texture, visual characteristics, and, where possible materials, so long as the applicant is able to provide one extant example, photographic evidence, or physical evidence that serves as the basis for the work proposed;

Construction of wooden decks that are at the rear of a structure and are not visible from a public right-of-way;

Roof replacement with -compatible roofing materials, or with architectural shingles replacing 3-Tab asphalt shingles;

Installation of storm windows or doors that are compatible with the historic resource or district;

Repair, replacement or installation of foundation-level doors, windows, window wells, and areaways, or foundation vents, venting pipes, or exterior grills that do not alter the character-defining features and/or the historic character of the resource;

Construction of fences that are compatible with the historic site or district in material, height, location, and design;

Fence is lower than 48" in front of rear wall plane;

Construction of walkways, parking pads, patios, driveways, or other paved areas that are not visible from a public right-of-way and measure no more than 150 square feet in size;

Replacement of existing walkways, parking pads, patios, driveways, or other paved areas with materials that are compatible with the visual character of the historic site and district and that are no greater than the dimensions of the existing hardscape;

Construction of small accessory buildings no larger than 250 square feet in size that are not visible from the public right-of-way;

Installations of skylights on the rear of a structure that will not be visible from the public right-of-way, and would not remove or alter character-defining roof materials;

Installation of solar panels and arrays in locations that are not readily visible from the public right-of-way or that are designed so as to have a minimal impact on the historic resource or the historic district (e.g., systems that are ground-mounted in areas other than the front or side yard of a corner lot, located on accessory or outbuildings, on non-historic additions, or on rear facing roof planes);

Installation of car charging stations in any location on a property or in the right-of-way;

Installation of satellite dishes;

Removal of trees greater than 6" in diameter (d.b.h.) that are dead, dying, or present an immediate hazard.

Removal of trees greater than 6" in diameter (d.b.h.) in the rear of the property that will not impact the overall tree canopy of the surrounding district or historic site;

Replacement tree required as a condition; and,

Other minor alterations that may be required by the Department of Permitting Services post-Commission approval that would have no material effect on the historic character of the property.

Staff finds the proposal complies with Chapter 24A, the Secretary of the Interior's Standards for Rehabilitation, and any additional requisite guidance. Under the authority of COMCOR No. 24A.04.01, this HAWP is approved by Christopher J. Berger on 12/11/23. The approval memo and stamped drawings follow.



**APPLICATION FOR
HISTORIC AREA WORK PERMIT**
HISTORIC PRESERVATION COMMISSION
301.563.3400

FOR STAFF ONLY:
HAWP# 1051671
DATE ASSIGNED _____

APPLICANT:

Name: Ryan Doyle
Address: 7317 Willow Avenue
Daytime Phone: 410-579-5172

E-mail: permitting@solarenergyworld.com
City: Takoma Park Zip: 20912
Tax Account No.: 01058654

AGENT/CONTACT (if applicable):

Name: Ryan Doyle
Address: 14880 Sweitzer Lane
Daytime Phone: 410-579-5172

E-mail: permitting@solarenergyworld.com
City: Laurel Zip: 20707
Contractor Registration No.: 127353

LOCATION OF BUILDING/PREMISE: MIHP # of Historic Pro

Is the Property Located within an Historic District? Yes/D
 No/In

Is there an Historic Preservation/Land Trust/Environmental
the Easeme

APPROVED
Montgomery County
Historic Preservation Commission

Ronald A. Motter

REVIEWED

By Chris Berger at 11:20 am, Dec 11, 2023
(Conditional Use, Variance, Record Plat, etc.?) if YES, include
supplemental information.

Building Number: 7317 Street: Willow Avenue
Town/City: Takoma Park Nearest Cross Street: Valley View Avenue
Lot: P22 Block: 8 Subdivision: 0025 Parcel: N/A

TYPE OF WORK PROPOSED: See the checklist on Page 4 to verify that all supporting items for proposed work are submitted with this application. Incomplete Applications will not be accepted for review. Check all that apply:

- | | | |
|---------------------------------------------|----------------------------------------------|----------------------------------------------------------|
| <input type="checkbox"/> New Construction | <input type="checkbox"/> Deck/Porch | <input type="checkbox"/> Shed/Garage/Accessory Structure |
| <input type="checkbox"/> Addition | <input type="checkbox"/> Fence | <input checked="" type="checkbox"/> Solar |
| <input type="checkbox"/> Demolition | <input type="checkbox"/> Hardscape/Landscape | <input type="checkbox"/> Tree removal/planting |
| <input type="checkbox"/> Grading/Excavation | <input type="checkbox"/> Roof | <input type="checkbox"/> Window/Door |
| | | <input type="checkbox"/> Other: _____ |

I hereby certify that I have the authority to make the foregoing application, that the application is correct and accurate and that the construction will comply with plans reviewed and approved by all necessary agencies and hereby acknowledge and accept this to be a condition for the issuance of this permit.

Ryan Doyle
Signature of owner or authorized agent

11/27/2013
Date

APPROVED

Montgomery County
Historic Preservation Commission



REVIEWED

By Chris Berger at 11:20 am, Dec 11, 2023

HAWP APPLICATION: MAILING ADDRESSES FOR NOTIFYING
[Owner, Owner's Agent, Adjacent and Confronting Property Owners]

Owner's mailing address Michael Fincham 7317 Willow Ave. Takoma Park MD 20912	Owner's Agent's mailing address Ryan Doyle 14880 Sweitzer Ln. Laurel MD 20707
Adjacent and confronting Property Owners mailing addresses	
Carla McGarvey 7315 Willow Ave. Takoma Park, MD 20912 Adjacent	Richard Smith 7319 Willow Ave. Takoma Park, MD 20912 Adjacent

Description of Property: Please describe the building and surrounding environment. Include information on significant structures, landscape features, or other significant features of the property:

Single Family Dwelling built in 1923.

Description of Work Proposed: Please give an overview of the work to be undertaken:

- Install (28) roof mounted solar panels
- Micro-Inverters to be installed under each panel
- Utility Disconnect to be installed next to utility meter along with electrical combiner box for micro-inverters
- Galvanized Steel Conduit to run from equipment along & tucked into attic.

REVIEWED

By Chris Berger at 11:20 am, Dec 11, 2023

APPROVED

Montgomery County

Historic Preservation Commission



Robert G. Patton

Historic Area Work Permit Application for Roof Mounted Solar
Michael Fincham, 7317 Willow Avenue, Takoma Park, MD 20912

REVIEWED
By Chris Berger at 11:20 am, Dec 11, 2023



Front View


APPROVED
Montgomery County
Historic Preservation Commission
Ronald A. Patton



East View



West View



Utility Side Example Before Installation



Utility Side Example After Installation

IQ8+

MICHAEL FINCHAM & ALI KAHN RESIDENCE NEW GRID-INTERACTIVE PHOTOVOLTAIC SYSTEM DC SYSTEM SIZE (6.205 KW)



SOLAR ENERGY WORLD
LLC, 5681 MAIN STREET
ELKRIDGE, MD 21075
(888) 497-3233

Signature with Seal

SYSTEM DETAILS

DESCRIPTION	NEW GRID-INTERACTIVE PHOTOVOLTAIC SYSTEM WITH NO BATTERY STORAGE
DC RATING OF SYSTEM	SYSTEM SIZE :6.205 KW DC STC
AC RATING OF SYSTEM	4.930 KW
AC OUTPUT CURRENT	20.57A
NO. OF MODULES	(17) HANWA Q CELL Q.PEAK DUO BLK-G10+ (365W) SOLAR MODULES
NO. OF INVERTERS	(17) ENPHASE IQ8PLUS-72-2-US MICROINVERTERS
POINT OF INTERCONNECTION	BACKFEED BREAKER IN THE MSP
ARRAY STRINGING	(1) BRANCHED CURCUIT OF 09 MODULES (1) BRANCHED CURCUIT OF 08 MODULES
UTILITY	PEPCO
AHJ	MONTGOMERY COUNTY

SITE DETAILS



ASHRAE EXTREME LOW	-12°C
ASHRAE 2% HIGH	34°C
GROUND SNOW LOAD	30 PSF
WIND SPEED	115MPH (ASCE 7-16)
RISK CATEGORY	II
WIND EXPOSURE CATEGORY	B

GOVERNING CODES

INTERNATIONAL BUILDING CODE (IBC) 2018
INTERNATIONAL FIRE CODE (IFC) 2018
INTERNATIONAL RESIDENTIAL CODE (IRC) 2018
NATIONAL ELECTRICAL CODE (NEC) 2017

SHEET INDEX

SHEET NO.	SHEET NAME
A - 00	SITE MAP & VICINITY MAP
A - 01	ROOF PLAN & MODULES
S - 01	ARRAY LAYOUT
S - 02	STRUCTURAL ATTACHMENT DETAIL
E - 01	ELECTRICAL LINE DIAGRAM
E - 02	WIRING CALCULATIONS
E - 03	SYSTEM LABELING
DS - 01	MODULE DATASHEET
DS - 02	MICROINVERTER DATASHEET
DS - 03	COMBINER DATASHEET
DS - 04	ATTACHMENT DATASHEET
SP-01	SAFETY PLAN



PROFESSIONAL CERTIFICATION, I HEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED OR APPROVED BY ME, AND THAT I AM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF MARYLAND
LICENSE NUMBER: 56915
EXPIRATION DATE: 12/16/2024

Signed: 11/14/2023


REVIEWED
By Chris Berger at 11:27 am, Dec 11, 2023

APPROVED
Montgomery County
Historic Preservation Commission
[Signature]


NOTES:

1. THE SYSTEM SHALL INCLUDE [17] Q.PEAK DUO BLK-G10+ (365W) SOLAR MODULES
2. SNAPRACK TOP SPEED MOUNT WILL BE INSTALLED IN ACCORDANCE WITH SNAPRACK INSTALLATION MANUAL
3. REFER TO STRUCTURAL DRAWING FOR SECTIONS MARKED AND ADDITIONAL NOTES


SITE MAP (N.T.S)



VICINITY MAP



WIND FLOW MAP



MICHAEL FINCHAM & ALI KAHN
MD 16942
7317 WILLOW AVE,
TAKOMA PARK, MD 20912

DISCLAIMER:
THIS DRAWING IS THE PROPERTY OF SOLAR ENERGY WORLD INC. THE INFORMATION HEREIN CONTAINED SHALL BE USED FOR THE SOLE BENEFIT OF SOLAR ENERGY WORLD. IT SHALL NOT BE DISCLOSED TO OTHERS OUTSIDE THE RECIPIENT'S ORGANIZATION, IN WHOLE OR IN PART, WITHOUT THE WRITTEN PERMISSION OF SOLAR ENERGY WORLD, EXCEPT IN CONNECTION WITH THE SALE AND USE OF THE RESPECTIVE SOLAR ENERGY EQUIPMENT.

PERMIT DEVELOPER
DATE: 11/14/2023
DESIGNER: ONG
REVIEWER:

SHEET NAME
SITE MAP & VICINITY MAP

SHEET NUMBER
A-00

ROOF DESCRIPTION:

(ROOF #1)

MODULES - 10
 ROOF TILT - 23°
 ROOF AZIMUTH - 211°
 TRUSS SIZE - 2"X6"@24" O.C.



(ROOF #2)

MODULES - 07
 ROOF TILT - 24°
 ROOF AZIMUTH - 121°
 TRUSS SIZE - 2"X6"@24" O.C.

Solar panels not to exceed a height of 6" from roof.




REVIEWED
 By Chris Berger at 11:27 am, Dec 11, 2023



PROFESSIONAL CERTIFICATION, I HEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED OR APPROVED BY ME, AND THAT I AM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF MARYLAND
 LICENSE NUMBER: 56915
 EXPIRATION DATE: 12/16/2024

Signed: 11/14/2023



LEGENDS

- FIRE SETBACK
- VENT, ATTIC FAN (ROOF OBSTRUCTION)
- PV ROOF ATTACHMENT
- CLAMP
- RAFTERS / TRUSSES

Signature with Seal

MICHAEL FINCHAM & ALI KAHN
 MD16942
 7317 WILLOW AVE,
 TAKOMA PARK, MD 20912


DISCLAIMER: THIS DRAWING IS THE PROPERTY OF SOLAR ENERGY WORLD INC. THE INFORMATION HEREIN CONTAINED SHALL BE USED FOR THE SOLE BENEFIT OF SOLAR ENERGY WORLD. IT SHALL NOT BE DISCLOSED TO OTHERS OUTSIDE THE RECIPIENT'S ORGANIZATION, IN WHOLE OR IN PART, WITHOUT THE WRITTEN PERMISSION OF SOLAR ENERGY WORLD, EXCEPT IN CONNECTION WITH THE SALE AND USE OF THE RESPECTIVE SOLAR ENERGY EQUIPMENT.

PERMIT DEVELOPER	
DATE	11/14/2023
DESIGNER	ONG
REVIEWER	
SHEET NAME	
ARRAY LAYOUT	
SHEET NUMBER	
S-01	


PHOTOVOLTAIC MODULE GENERAL NOTES:

1. APPLICABLE CODE: INTERNATIONAL RESIDENTIAL CODE 2018
MINIMUM DESIGN LOADS FOR BUILDING AND OTHER STRUCTURES
2. BOLT DIAMETER AND EMBEDMENT LENGTHS ARE DESIGNED PER NDS REQUIREMENTS. ALL BOLT CAPACITIES ARE BASED ON A WOOD ROOF TRUSS AS EMBEDMENT MATERIAL.
3. ALL WIND DESIGN CRITERIA AND PARAMETERS ARE FOR HIP AND GABLE RESIDENTIAL ROOFS, CONSIDERING FROM A 7° TO A MAXIMUM 45° (2/12 TO A MAXIMUM 9/12 PITCH) ROOF IN SCHEDULE. ALL RESIDENTIAL ROOFS SHALL NOT EXCEED 30'-0" MEAN ROOF HEIGHT.
4. ROOF SEALANTS SHALL CONFORM TO ASTM C920 AND ASTM 6511.
5. THIS SHEET REFLECTS STRUCTURAL CONNECTIONS ONLY. REFER TO MANUFACTURERS' MANUAL FOR ALL ARCHITECTURAL, MECHANICAL, ELECTRICAL, AND SOLAR SPECS.
6. ALL ALUMINUM COMPONENTS SHALL BE ANODIZED ALUMINUM 6105-T5 UNLESS OTHERWISE NOTED.
7. LAG BOLTS SHALL BE ASTM A276 STAINLESS STEEL UNLESS OTHERWISE NOTED.
8. ALL RAILING AND MODULES SHALL BE INSTALLED PER MANUFACTURERS' INSTRUCTIONS.
9. I CERTIFY THAT THE INSTALLATION OF THE MODULES IS IN COMPLIANCE WITH INTERNATIONAL RESIDENTIAL CODE 2018 AND INTERNATIONAL BUILDING CODE 2018. BUILDING STRUCTURE WILL SAFELY ACCOMMODATE CALCULATED WIND LATERAL AND UPLIFT FORCES, AND EQUIPMENT DEAD LOADS.

Solar panels not to exceed a height of 6" from roof.




ATTACHMENT DETAIL



REVIEWED

By Chris Berger at 11:27 am, Dec 11, 2023



PROFESSIONAL CERTIFICATION, I HEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED OR APPROVED BY ME, AND THAT I AM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF MARYLAND
LICENSE NUMBER: 56915
EXPIRATION DATE: 12/16/2024

Signed: 11/14/2023

APPROVED
Montgomery County
Historic Preservation Commission

STRUCTURAL ATTACHMENT DETAILS FOR ASPHALT SHINGLE

Signature with Seal

MICHAEL FINCHAM & ALI KAHN
MD16942

7317 WILLOW AVE,
TAKOMA PARK, MD 20912

DISCLAIMER:
THIS DRAWING IS THE PROPERTY OF SOLAR ENERGY WORLD INC. THE INFORMATION HEREIN CONTAINED SHALL BE USED FOR THE SOLE BENEFIT OF SOLAR ENERGY WORLD. IT SHALL NOT BE DISCLOSED TO OTHERS OUTSIDE THE RECIPIENT'S ORGANIZATION, IN WHOLE OR IN PART, WITHOUT THE WRITTEN PERMISSION OF SOLAR ENERGY WORLD, EXCEPT IN CONNECTION WITH THE SALE AND USE OF THE RESPECTIVE SOLAR ENERGY EQUIPMENT.

PERMIT DEVELOPER	
DATE	11/14/2023
DESIGNER	ONG
REVIEWER	
SHEET NAME	
STRUCTURAL ATTACHMENT DETAILS	
SHEET NUMBER	
S-02	



APPROVED

Montgomery County
Historic Preservation Commission



REVIEWED

By Chris Berger at 11:27 am, Dec 11, 2023

SnapNrack™

Solar Mounting Solutions

TopSpeed™ Mounting System

Installation Manual

snapnrack.com

SnapNrack's primary goal is to provide our customers with the lowest possible installed cost for mounting residential solar modules, without compromising the values the industry has come to expect: ease of use, quality, aesthetics, and safety. Designing with this goal in mind, we are proud to present the SnapNrack TopSpeed™ mounting system with SpeedSeal™ Technology.

SnapNrack has created a ground breaking system combining great features and benefits we are known for, with our TopSpeed™ System and the most up to date technical innovation in the industry, thus reducing parts while driving down labor, material, and total installation costs. Designed to work with standard module frames, achieving UL 2703 Listing for Grounding/Bonding and Fire Classification, providing integrated wire management, aesthetics and our industry leading "Snap-In" features, SnapNrack is providing the simplest and most cost effective solar mounting solution on the market with TopSpeed™ including integrated fasteners and SpeedSeal™ Technology.

Advantages of Installing the SnapNrack TopSpeed™ System

Modules are installed with a minimum number of parts

This elimination of parts leads to a lower estimated system cost for both the installer and home owner.

Built in Wire Management and Aesthetics

Extensive wire management solutions have been designed specifically for the system that adapts to multiple possible mounting positions.

The system is designed to be aesthetically pleasing and sturdy with a skirt that provides considerable strength at the leading edge and an elegant look for those seeking high end looking systems.

SnapNrack TopSpeed™ includes SpeedSeal™ Technology

SpeedSeal™ Technology features integrated flashing. This eliminates loosening layers of composition and removing nails with a pry bar, leading to less damage to the roof, minimized potential roof leaks, and much faster installs.

TopSpeed™ Mounts attach Directly to the Decking

As well as all of the benefits associated with the standard SpeedSeal™ Technology, TopSpeed™ attaches to the roof sheathing and does not require rafter attachment. Simply attaching to the roof sheathing removes the requirement for finding rafters and drilling pilot holes, creating potential rafter misses that can cause leaks.

REVIEWED

By Chris Berger at 11:27 am, Dec 11, 2023

APPROVED

Montgomery County

Historic Preservation Commission



Project Plans

Certification Details 4

Component Details 5

Pre-Installation Requirements 7

Installation Steps

TopSpeed™ Skirt Layout 8

TopSpeed™ Mount to Module Installation 9

TopSpeed™ Mount Skirt Installation 10

Wire Management 13


MLPE Attachment 16

Module Installation 19

Grounding Specifications 22

Maintaining the Grounding Bonding When Removing a Module 23

Appendix A: List of approved Modules and MLPEs 25



Certification Details

SnapNrack TopSpeed™ mounting system has been evaluated by Underwriters Laboratories (UL) and Listed to UL Standard 2703 for Grounding/Bonding, and Fire Classification.

Grounding/Bonding

Only specific components have been evaluated for bonding, and are identified as being in the ground path. The TopSpeed™ components that have been evaluated for bonding are the Mount Assembly (Mount Clamp Top, Module Clamp Tower, Angle Bracket), Clamp Assembly, Universal Skirt, Universal Skirt Clamp, Ground Lugs, and Smart Clips.

Universal Skirt Spacers, Mount Channel Nut, and Mount Base are not required to be bonded to the system based on the exceptions in clause 9.1 of UL 2703 1st Ed. Wire management clips are utilized to route conductors away from these components and must be assembled according to the instructions.

This mounting system may be used to ground and/or mount a PV module complying with UL 1703 or UL 61703 only when the specific module has been evaluated for grounding and/or mounting in compliance with the included instructions. See Appendix A for the list of modules tested for use with the TopSpeed™ System for integrated grounding.

Ground Lugs have been evaluated to both UL 467 and UL 2703 Listing requirements. The following ground lugs have been approved for use: SnapNrack model 242-92202, and IlSCO models GBL-4DBT and SGB-4.

The following components have been evaluated for bonding as the fault current ground path: TopSpeed™ Mount Assembly, (Mount Clamp Top, Module Clamp Tower, Angle Bracket), Clamp Assembly, Wire Management Clips, and Ground Lugs. In order to maintain the Listing for bonding, wire management clips must be assembled to route conductors away from parts that have not been evaluated for bonding.

A Listed (QIMS) and Unlisted Component (KDER3) grounding lug, SnapNrack part no. 242-92202, is attached to the module frame flange for the normal attachment of a Grounding Electrode Conductor, which provides bonding within the system and eventual connection to a Grounding Electrode, as required by the U.S. NEC. Details of part no. 242-92202 can be found in Volume 1, Section 4, and Volume 2, Section 2. When this method is used, the grounding symbol is stamped onto the body of the ground lug to identify the grounding terminal.

An alternate method of grounding, a UL Listed (KDER and QIMS) grounding lug, IlSCO (E34440 and E354420) model SGB-4 is attached to the module frame flange. When this method is used, the grounding terminal is identified by the green colored screws of the lug.

APPROVED

Montgomery County

Historic Preservation Commission



ng, a UL Listed (KDER and QIMS) grounding lug, IlSCO (E34440 and E354420) model SGB-4 is attached to the module frame flange through the specified hardware and when this method is used, the grounding terminal is identified by the green colored set

ng, Enphase R/C (QIKH2)(QIMS2) model M250, M215 & C250 is bonded to ground through the Enphase R/C (QIMS2) Model EFM-XXMM anodization piercing device. A roof-mounted PV system is bonded (modules and microinverters) to ground through the Enphase R/C (QIMS2) Engage Cables; ETXX-277, when properly grounded at the service entrance.

(6) photovoltaic bonding device cat. no. Dynobond is an optional component that may be used with this system. The Dynobond device has been evaluated to provide module to module bonding. The Dynobond device attaches to the frame flange of adjacent modules

UL Listed SnapNrack MLPE Frame Attachment Kit model 242-02151 has been investigated to bond device back plates to frames of modules.

REVIEWED

By Chris Berger at 11:27 am, Dec 11, 2023

Fire

SnapNrack TopSpeed™ has been investigated for a Class A System Fire Classification for Steep-Sloped and low sloped roofs with Type 1 and Type 2 modules. Because the system was tested at 5 inches above the test roof fixture, TopSpeed™ can be installed without any height restrictions due to System Fire Classification. See Appendix A for potential module-specific height restrictions due to module temperature. The Skirt is considered an optional component with respect to Fire Classification, as SnapNrack TopSpeed™ maintains the same Fire Classification Rating both with and without the skirt.

NOTE: Modules with an asterisk* have a fire rating that is different from Type 1, Type 2 or Type 29. SNR systems have only been evaluated for use with Type 1, Type 2, or Type 29 modules. Modules with a different fire type rating should be considered to not have been evaluated for use with SNR systems with respect to a system fire rating.

Inspection Practices

SnapNrack recommends a periodic re-inspection of the completed installation for loose components, loose fasteners, and any corrosion, such that if found, the affected components are to be immediately replaced.

APPROVED

Montgomery County

Historic Preservation Commission



REVIEWED


By Chris Berger at 11:27 am, Dec 11, 2023

TopSpeed™ Structural Components



TopSpeed™ Mount

SnapNrack TopSpeed™ Mount assembly including SpeedSeal™ base, clamp top, and (4) SnapNrack #14 SS Wood Screws with 1/2" Hex Head.




TopSpeed™ Clamp

SnapNrack TopSpeed™ Clamp assembly including including Link bottom, Link top, and springs.




Universal Skirt

SnapNrack Universal Skirt in double portrait or single landscape lengths.




Skirt Spacers

SnapNrack Universal Skirt Spacer for 40mm, 38mm, 35mm, 32mm, and 30mm modules.



Smart Clip

Module frame cable clip, holds two PV wires or Enphase IQ-Cables.



Smart Clip XL

Module frame cable clip, holds six PV wires or four Enphase IQ-Cable.




Wire Saver

Designed to secure conductors that are being pulled below the array, holds one conductor.


REVIEWED
By Chris Berger at 11:27 am, Dec 11, 2023

Grounding/MLPE Components



Ground Lug

SnapNrack Ground Lug assembly used for attaching the Equipment Grounding Conductor on to one any TopSpeed™ Mount per array.



MLPE Frame Attachment Kit

Attaches MLPEs (Module Level Performance Enhancers) and other related equipment to the module frame.

Hardware Torque Specifications

The recommended torque to be applied to components for proper assembly and bonding are as follows:

Hardware Description	Torque Specification
All TopSpeed™ ½" bolts; System Leveling Bolt, TopSpeed™ Mount Clamping Bolt, Clamp Bolt	16 ft-lb
Ground Lug model 242-92202 to Module Frame or anywhere on the TopSpeed™ Mount, and Ground Lug model 242-92202 to Grounding Electrode Conductor (6-12 SOL)	8 ft-lb
MLPE Frame Attachment Kit, MLPE Rail Attachment Kit	10 ft-lb
SolarEdge Frame Mounted Microinverter Bracket to Module Frame	11 ft-lb
Enphase Frame Mounted Microinverter Bracket to Module Frame	13 ft-lb
Ground Lug model SGB-4 to module	75 in-lb
Ground Lug model SGB-4 to Grounding Electrode Conductor (4-14 SOL or STR)	35 in-lb
Ground Lug model GBL-4DBT to module	35 in-lb
Ground Lug model GBL-4DBT to Grounding Electrode Conductor (10-14 SOL or STR)	20 in-lb
Ground Lug model GBL-4DBT to Grounding Electrode Conductor (8 SOL or STR)	25 in-lb
Ground Lug model GBL-4DBT to Grounding Electrode Conductor (4-6 SOL or STR)	35 in-lb

APPROVED
Montgomery County
Historic Preservation Commission



REVIEWED
By Chris Berger at 11:27 am, Dec 11, 2023

Site Survey

- Measure the roof surfaces and develop an accurate drawing, including any obstacles such as chimneys and roof vents.
- If plans for the roof structure are available, verify that the plans match the final structure.
- Identify any roof access or setback areas as required by the local AHJ.
- Identify any construction issues that may complicate the process of locating rafters from the roof surface.
- If you find structural problems such as termite damage or cracked rafters that may compromise the structure's integrity consult a structural engineer.





Image note: X-Axis described in this manual is cross-slope on the roof, Y-Axis is in line with the roof slope.



0.75 inch spacing when creating the layout.

ing the engineering versions comply with

specifications in part to determine the



- Insert SnapNrack installation details into design plan set specific to the project requirements.

REVIEWED

Draw roof attachment locations on plan set layout based on
By Chris Berger at 11:27 am, Dec 11, 2023

Best Practice:

If environmental load conditions require three TopSpeed™ attachments per module side this is only required when modules share attachments.

- Identify homerun and Junction Box locations based on rooftop wiring requirements.
- Mark distance from array edge to identifiable roof feature in x and y axes.




Image note: This four module array is installed in a high load configuration with three attachments per side where two modules share attachments. See highlighted area. As shown, three attachments are never required at the skirt or the top of the array.

Safety Guidance

- Always wear appropriate OSHA approved safety equipment when at active construction site.
- Appropriate fall protection or prevention gear should be used. Always use extreme caution when near the edge of a roof.
- Use appropriate ladder safety equipment when accessing the roof from ground level.

Safety Guidance Continued

- Safety equipment should be checked periodically for wear and quality issues.
- Always wear proper eye protection when required.

Required Tools

● Socket Wrench/Impact Driver

● Torque Wrench

● 1/2" Socket

Materials Included - TopSpeed™ System with SpeedSeal™ Technology

- 1 (1) SnapNrack TopSpeed™ Mount
- 2 (4) SnapNrack #14 Wood Screw with 1/2" Hex Head & sealing washer

Best Practice:



Attach all TopSpeed™ mounts as the modules are being prepped with MLPEs on the ground. Attach Mounts before attaching MLPEs to simplify wire management.

APPROVED


Montgomery County
Historic Preservation Commission




INSTALLATION INSTRUCTIONS



1) Assemble all TopSpeed™ Mounts required for the installation. Slide the clamp tower assembly into the angle bracket riser and tighten the leveling bolt to 16 ft-lbs.



2) Position TopSpeed™ Mount clamp on the module frame within the module manufacturers required clamping zone.



3) Tighten 1/2" clamping bolt to 16 ft-lb. Only two Mounts are required per module on one side.

Install Note:

For high load conditions add a third attachment in the middle of the module frame.

REVIEWED

By Chris Berger at 11:27 am, Dec 11, 2023

Required Tools

- Roof Marking Crayon or Chalk
- Tape Measure


LAYOUT INSTRUCTIONS

1) Use a tape measure to verify that all modules will fit properly on the roof surface.

2) On the roof draw the layout for the skirt installation including module gaps (recommended 0.75 inch gap), bottom corners, and locations of the two TopSpeed™ attachments per module that clamp to the skirt. Three attachments per module is never required at the skirt.

Install Note:

If environmental load conditions require three TopSpeed™ attachments per module side this is only required when modules share attachments.



APPROVED

Montgomery County

Historic Preservation Commission

A handwritten signature in black ink, appearing to read "Robert L. Adams", is written over a horizontal line.

REVIEWED


By Chris Berger at 11:27 am, Dec 11, 2023

Required Tools

- Socket Wrench/Impact Driver
- Torque Wrench
- 1/2" Socket
- Roofing sealant

Materials Included - TopSpeed™ Mount with SpeedSeal™ Technology


- ① (1) TopSpeed™ Mount
- ② (1) TopSpeed™ Clamp
- ③ (1) Universal Skirt
- ④ (1) Universal Skirt Spacers
- ⑤ (1) *OPTIONAL* - Universal Link




APPROVED
Montgomery County
Historic Preservation Commission
Robert A. Potter

REVIEWED
By Chris Berger at 11:27 am, Dec 11, 2023


INSTALLATION INSTRUCTIONS



1) Install TopSpeed™ Mounts at locations drawn during the skirt layout. Mounts must be installed entirely on one course of composition.



2) Fill both cavities on bottom of TopSpeed™ Mount created by SpeedSeal™ gasket with roof sealant to ensure a watertight seal.




3) Attach TopSpeed™ Mount to roof using the (4) SnapNrack #14 Wood Screws with 1/2" hex head that are captured in the Mount.

Install Note:


Roof sealant should be expelled from both vents of the TopSpeed™ Mount as it is installed to assure the proper amount of roof sealant has been applied. If sealant is not expelled from all four vents, remove TopSpeed™ Mount, add more sealant to the cavity, then reinstall.

REVIEWED


By Chris Berger at 11:27 am, Dec 11, 2023



4) Loosen Course Adjustment bolt and adjust end Mounts up or down until aligned with bottom edge of array as marked on the roof, then tighten the Course Adjustment bolt.



5) To set the TopSpeed™ Mount level loosen the Leveling bolt and move the clamp up or down, then tighten the Leveling bolt and torque to 16 ft-lb.



6) Pull string line tight from one corner mount to opposite corner mount to align and level all TopSpeed™ Mounts between the end mounts.



Install Note:

Use the string line alignment feature on Mounts to level and align the Mounts.


APPROVED

Montgomery County
Historic Preservation Commission



INSTALLATION INSTRUCTIONS



7) Universal Spacers will need to be added to Mounts and Clamps where Skirt will be installed.



8) Install Universal Skirt by holding the skirt in Mount, sliding Skirt to align with array layout marks, and clamping skirt into mount.



9) Use TopSpeed™ Clamps to connect multiple lengths of Array Skirt.



Install Note:

Optionally use Universal Links to connect lengths of Array Skirt.

APPROVED

Montgomery County

Historic Preservation Commission

REVIEWED

By Chris Berger at 11:27 am, Dec 11, 2023


Required Tools

- Socket Wrench
- Torque Wrench
- 1/2" Socket
- Electrician Tools


Materials Included

Smart Clips


- 1 (1) Smart Clip [(2) PV Wire, (1) Enphase IQ Cable]
- 2 (1) Smart Clip XL [(6) PV Wire, (4) Enphase IQ]
- 3 (1) Wire Saver [(1) PV Wire]



Smart Clip



Smart Clip XL



Wire Saver

APPROVED

Montgomery County


Historic Preservation Commission

REVIEWED


By Chris Berger at 11:27 am, Dec 11, 2023

INSTALLATION INSTRUCTIONS - GROUND LUG


The SnapNrack Ground Lug to be used in accordance with the National Electric Code, ANSI/NFPA 70.




1) Ground Lug (242-92202) can be attached anywhere along the module frame or any TopSpeed™ Mount near the Junction Box. Torque module clamping bolt to 8 ft-lb.



2) Run 10 - 6 AWG, solid, bare copper GEC into Ground Lug channel, torque wire clamping bolt to 8 ft-lb.



3) Run bare, solid EGC from Ground Lug R to Junction Box, bond bare EGC to stranded EGC in Junction Box. For details on installing the Junction Box reference the **Junction Box Installation Manual**.



4) Optionally; Install Ground Lug on the Mount Landing Pad at the top of the array. Run bare copper between ground lug and Junction Box.

APPROVED
Montgomery County
Historic Preservation Commission




REVIEWED


By Chris Berger at 11:27 am, Dec 11, 2023

INSTALLATION INSTRUCTIONS - SMART CLIPS

SmartClip and SmartClip XL should be used to route conductors in a neat and workmanlike manner away from all non-bonded components and support the conductors adequately to eliminate potential damage.



1) Use SnapNrack Smart Clip II to manage up two PV wires inside the module frame while prepping out the modules on the ground or installing modules on the roof.



2) Use SnapNrack Smart Clip XL to manage larger bundles of PV wire; up to 6 PV wires per clip



REVIEWED



By Chris Berger at 11:27 am, Dec 11, 2023

Required Tools

- Socket Wrench
- Torque Wrench
- 1/2" Socket

Materials Included - MLPE Rail Attachment Kit

- 1 (1) SnapNrack MLPE Frame Attachment Top
- 2 (1) SnapNrack MLPE Frame Attachment Bottom
- 3 (1) 5/16"-18 X 3/4" Serrated Flange Bolt SS
- 4 (1) SnapNrack Smart Clip
- 5 (1) SnapNrack MLPE Frame Attachment Coil Spring SS




REVIEWED

By Chris Berger at 11:27 am, Dec 11, 2023

Materials Included


SolarEdge Frame Mount

- 1 (1) SolarEdge Optimizer w/ Frame-Mounted Module Add-On



Enphase Frame Mount

- 1 (1) Enphase Microinverter
- 2 (1) Enphase Frame Mount




APPROVED
Montgomery County
Historic Preservation Commission


A handwritten signature in black ink, reading "Robert H. Butler".

INSTALLATION INSTRUCTIONS - SNAPNRACK MLPE FRAME ATTACHMENT KIT


SnapNrack MLPE Frame Attachment kit are used to attach module level performance enhancing devices, and other devices such as an SRD (rapid shutdown device), directly to module frames, and provide integrated grounding/bonding for Devices grounded through metal back plate. (Refer to the list of tested MLPE devices on page XX of this manual).



1) Slide the backplate channel of the MLPE device under the MLPE Frame Attachment Kit bolt. The MLPE mounting plate should rest against the MLPE mounting plate backstop on the MLPE Frame Attachment Kit.



2) Position the MLPE Frame Attachment Kit on the module frame flange in a location that will not interfere with mounting system components. The module frame flange should rest against the module flange backstop on the MLPE Frame Attachment Kit.



3) Tighten the mounting bolt on the MLPE Frame Attachment Kit to 12 lb-ft (144 lb-in).




Install Note:

The MLPE Frame Attachment Kit bonds the following components: Module Frame, MLPE backplate and Smart Clip.



Install Note:

Avoid blocking module frame drainage holes when installing the MLPE Frame Attachment Kit.



4) Connect the module leads to the input connectors on the MLPE device and manage conductors with the integrated Smart Clip.


APPROVED

Montgomery County
Historic Preservation Commission


REVIEWED

By Chris Berger at 11:27 am, Dec 11, 2023


INSTALLATION INSTRUCTIONS - SOLAREGE FRAME MOUNT



1) Locate the SolarEdge optimizer with Frame-Mounted Module Add-On at a location on the module frame that will not interfere with the TopSpeed™ Mounts.



2) Install the optimizer mounting plate onto the module frame and tighten hardware to 11 ft-lbs.




3) Connect the module leads to the input connectors on the optimizer and manage conductors with SnapNrack Smart Clips.




Install Note:

If module is mounted in portrait, install MLPE on long side, short side for landscape.

INSTALLATION INSTRUCTIONS - ENPHASE FRAME MOUNT



1) Locate the Enphase Frame Mount bracket clamp at a location on the module frame that will not interfere with the TopSpeed™ Mounts.




2) Slide the microinverter unit onto the bracket clamp, then move it slightly to the left.



Install Note:

The microinverter mounting flange should be on the outside of the module frame.



3) Tighten the hardware to 13 ft-lbs.

4) Connect module leads to microinverter DC connectors.



Install Note:

Refer to the Enphase Frame Mount installation guide for additional instructions.

APPROVED

Montgomery County

Historic Preservation Commission

REVIEWED


By Chris Berger at 11:27 am, Dec 11, 2023

Required Tools

- Socket Wrench
- Torque Wrench
- 1/2" Socket
- Roofing Sealant




Materials Included

- ① SnapNrack TopSpeed™ Mount
- ② SnapNrack TopSpeed™ Clamp



Other Materials Required

- ② SnapNrack Smart Clip (2-5 per module)
See Wire Management section for details
- ③ SnapNrack Smart Clip XL (10-20 per array)
See Wire Management section for details



INSTALLATION INSTRUCTIONS - BOTTOM ROW


Recommended Best Practice:

Attach all TopSpeed™ mounts as the modules are being prepped with MLPEs on the ground. Attach Mounts before attaching MLPEs to simplify wire management.


Install Note:

It is recommended that module leads and connectors are prepared for installation using SnapNrack Smart Clips before being brought to the rooftop.


- With no MLPE, secure module leads to module frame to allow access to connectors while modules are installed
- Secure MLPE device to module frame with SnapNrack MLPE Frame Attachment Kit and connect module leads to MLPE, and manage leads by positioning connectors to allow access during installation





1) Rest downslope edge of module on the Mounts and/or Clamps position module so side edge is flush with marked edge of array layout or Skirt.



2) Lower upslope edge of module while simultaneously applying slight pressure to seat module into Mounts and/or Clamps.



3) When module is level with roof verify the Speedseal™ portion of the TopSpeed™ Mounts are positioned entirely on one course of composition. If required listen the 1/2" nut and adjust the base as needed then tighten the bolt.



4) Lift the upslope edge of the module and fill the SpeedSeal™ reservoir with roofing sealant.


Install Note:

Roof sealant should be expelled from both vents of the TopSpeed™ Mount as it is installed to assure the proper amount of roof sealant has been applied. If sealant is not expelled from all four vents, remove TopSpeed™ Mount, add more sealant to the cavity, then reinstall.


REVIEWED

By Chris Berger at 11:27 am, Dec 11, 2023


INSTALLATION INSTRUCTIONS - BOTTOM ROW



5) Lower the module to the roof and drive the (4) pre installed Snapnrack #14 Wood Screws with 1/2" hex head into the roof sheathing.



6) Repeat steps 1 through 5 for additional modules in the array.



7) For staggered arrays and arrays with mixed orientation, use the TopSpeed™ Clamp as needed to support the modules.

Install Note:

Roof sealant should be expelled from both vents of the TopSpeed™ Mount as it is installed to assure the proper amount of roof sealant has been applied. If sealant is not expelled from both vents, remove TopSpeed™ Mount, add more sealant to the cavity, then reinstall.

When installing a TopSpeed™ Clamp for support of an over cantilevered module, the clamp shall be installed 2-6" from the edge of the upslope (cantilevered) module.

APPROVED

Montgomery County

Historic Preservation Commission



REVIEWED

By Chris Berger at 11:27 am, Dec 11, 2023

GROUND PATH DETAILS

All TopSpeed™ components in the fault current ground path have been Certified to be used

APPROVED
 Montgomery County
 Historic Preservation Commission





- SnapNrack, TopSpeed™ Mount
- SnapNrack, TopSpeed™ Clamp

REVIEWED


By Chris Berger at 11:27 am, Dec 11, 2023

ing. The maximum or Ground Code National to select the Conductor ent of the PV


owing current ground





GROUNDING METHOD DETAILS




1) Row to row module bonding provided by bonding clips in Mount assembly and Clamp assembly.



2) Column to column bonding provided by Universal Skirt and bonding clips in the Clamp assembly and/or the RL Universal Link assembly. Module heights evaluated for bonding with Link Bonding Clamps: 40mm, 38mm, 35mm, 32mm, 30mm



3) Each continuous array is connected to Equipment Grounding Conductor through Ground Lug (242-92202) installed on one module per array.



GROUNDING MARKING DETAILS

The Ground Lug is marked with the ground symbol.

Optionally; Install Ground Lug on the Mount Landing Pad at the top of the array.

Maintaining the Grounding Bonding When Removing a Module

INSTRUCTION FOR MAINTAINING THE GROUNDING BONDING WHEN REMOVING A MODULE FOR SERVICING

CAUTION: Module removal may disrupt the bonding path and could introduce the risk of electric shock. Additional steps may be required to maintain the bonding path. Modules should only be removed by qualified persons in compliance with the instructions in this manual.

Module removal is not presented as a frequently expected occurrence and will not be required as part of routine maintenance.



Scenarios that could result in a disruption of the bonding path are described, for example irregularly-shaped arrays, arrays consisting of individual rows, and any other scenario where module removal could disrupt the bonding path. In most cases, the removal of a module for servicing will not disturb or break grounding continuity. If a module is to be removed that will break continuity, these are the steps that must be taken to maintain a continuously bonded SnapNrack TopSpeed™ System.

Required Tools

- Socket Wrench
- Torque Wrench
- 1/2" Socket
- 7/16" Socket

Required Materials

- 1 #10 Or Larger Bare Copper Conductor
- 2 SnapNrack Ground Lug part no. 242-92202
- 3 IlSCO Part No. SGB-4
- 4 DnoRaxx Dynobond™



APPROVED
Montgomery County
Historic Preservation Commission




REVIEWED
By Chris Berger at 11:27 am, Dec 11, 2023

Maintaining the Grounding Bonding When Removing a Module

JUMPER ASSEMBLY INSTRUCTION & INSTALLATION

CAUTION: Do Not Remove the Module until the Jumper is installed


1) Identify the existing ground path at the location of module removal and choose an appropriate length of #10 bare copper to bridge the soon to be broken ground path.



Example of assembled bonding jumper using (2) SnapNrack Ground Lugs

2) Attach one ground lug to each end of #10 bare copper wire. See recommended options below:

1. (2) SnapNrack Ground Lug part no. 242-922022
2. (2) IlSCO part no. SGB-4
3. (1) DroRaxx DynoBond™



3) Before the module is removed, attach the assembled bonding jumper. Depending on where the module will be removed and choice of ground lug, jumper attachment locations will vary.

- SnapNrack Ground Lug part no. 242-92202 or IlSCO SGB-4 lugs can be attached to module frames or anywhere on the TopSpeed™ Mount.
- DynoRaxx DynoBond™ is approved and appropriate when a short bonding jumper is needed from module to module.

4) Service the array. With the bonding jumper installed, it is now safe to remove the module for service or maintenance.

5) After Servicing the array reinstall the module and original ground path. Only then Remove the bonding jumper.

Caution: Do not remove the bonding jumper until original ground path is established.



REVIEWED

By Chris Berger at 11:27 am, Dec 11, 2023

APPROVED MODULE & MLPE INFORMATION

SnapNrack TopSpeed™ System has been tested with the following UL Listed module series: The SnapNrack TopSpeed™ System employs top-down clamps and links which have been evaluated for frame-to-system bonding, at specific mounting torques and with the specific module series listed below. All wattage values are covered.


Module manufacturer approval letters can be found at www.snaprack.com.


Manufacturer	Model	
Aptos Solar	DNA-120-MF23-XXX	DNA-120-BF26-XXXW
	DNA-120-BF23-XXX	DNA-144-BF26-XXXW
	DNA-144-MF23-XXX	DNA-108-BF10-xxxW
	DNA-144-BF23-XXX	DNA-120-BF10-xxxW
	DNA-120-MF26-XXXW	DNA-108-MF10-xxxW
	DNA-144-MF26-XXXW	
	CS6K-XXX-M	CS1H-XXX-MS
	CS6K-XXX-M-SD	CS1H-XXX-MS-AB
	CS6K-XXX-P	CS3W-XXX-P
	CS6K-XXX-P-SD	CS3N-XXX-MS
CS6K-XXX-MS	CS1Y-XXX-MS	
CS3K-XXX-P	CS3W-MB-AG	
CS3K-XXX-MS	CS3Y-MB-AG	
CS3U-XXX-MS	CS6W-XXXMB-AG	
CS3U-XXX-P	CS6R-XXXMS-HL	
CS1K-XXX-MS	CS3W-XXX-MS	
CTXXXHC11-06		
Chint Solar	CHSM6612M-XXX	CHSM72M-HC-XXX* (Astro 4)
	CHSM6612M(BL)-XXX	CHSM72M-HC-XXX* (Astro 5)
	CHSM6612M/HV-XXX	
Dehui Solar	DH-M760B-XXXW	DH-M760F-XXXW
	DH-M760W-XXXW	DH-M772F-XXXW
	DH-M772W-XXXW	
Freedom Forever	FF-MP-BBB-xxx	
Hanwha Q Cells	Q.PEAK DUO-G5-XXX	Q.PEAK DUO XL-G10.3/BFG-XXX
	Q.PEAK DUO-BLK-G5-XXX	Q.PEAK DUO G10-XXX
	Q.PLUS DUO-G5-XXX	Q.PEAK DUO BLK G10-XXX
	Q.PEAK DUO-G7-XXX	Q.PEAK DUO G10+-XXX
	Q.PEAK DUO-BLK-G7-XXX	Q.PEAK DUO BLK G10+-XXX
	Q.PEAK DUO-G7.2-XXX	Q.PEAK DUO XL-G10.3-XXX
	Q.PEAK DUO-G6+-XXX	Q.PEAK DUO XL-G10.c-XXX
	Q.PEAK DUO-BLK-G6+-XXX	Q.PEAK DUO XL-G10.d-XXX
	Q.PEAK DUO-G6-XXX	Q.PEAK DUO L-G8.3/BFG-XXX
	Q.PEAK DUO-BLK-G6-XXX	Q.PEAK DUO L-G8.3/BGT-XXX
	Q.PEAK DUO-G8+-XXX	Q.PEAK DUO ML-G10-XXX
	Q.PEAK DUO-BLK-G8+-XXX	Q.PEAK DUO BLK ML-G10+-XXX


APPROVED
Montgomery County
Historic Preservation Commission



REVIEWED
By Chris Berger at 11:27 am, Dec 11, 2023

Manufacturer	Model	
<p style="text-align: center;">APPROVED</p> <p style="text-align: center;">Montgomery County Historic Preservation Commission</p> 	Q.PEAK DUO-G8-XXX	Q.PEAK DUO ML-G10+-XXX
	Q.PEAK DUO-BLK-G8-XXX	Q.PEAK DUO BLK ML-G10-XXX
	Q.PEAK DUO BLK-G6+/AC-XXX	Q.PEAK DUO ML-G10.a+-XXX
	Q.PEAK DUO-ML-G9-XXX	Q.PEAK DUO BLK ML-G10.a+-XXX
	Q.PEAK DUO-BLK-ML-G9-XXX	Q.PEAK DUO ML-G10.a-XXX
	Q.PEAK DUO-BLK-G9-XXX	Q.PEAK DUO BLK ML-G10.a-XXX
	Q.PEAK DUO-BLK-ML-G9+-XXX	Q.PEAK DUO BLK G10+/AC XXX
	Q.PEAK DUO-ML-G9+-XXX	Q.PEAK DUO BLK G10+/HL XXX
	Q.PEAK DUO-BLK-ML-G9+-XXX	Q.PEAK DUO XL-G11.3 XXX
	Q.PEAK DUO XL-G9.2-XXX	Q.PEAK DUO XL-G11.3 BFG XXX
	Q.PEAK DUO XL-G9.3-XXX	Q.TRON-G1+ XXX
	Q.PEAK DUO XL-G9.3/BFG-XXX	Q.TRON BLK-G1+ XXX
	<p style="text-align: center;">REVIEWED</p> <p style="text-align: center;">By Chris Berger at 11:27 am, Dec 11, 2023</p>	Q.PEAK DUO ML-G10.2-XXX
HT60-168M-XXX		HT60-182M-XXX
60P-XXX		72M-XXX
<p style="text-align: center;">"Hyundai (All may be followed by "BK")"</p>	HiA-SXXXMS	HiS-SXXXVI
	HiS-SXXXXY	HiS-SXXXVIH(BK)
Hyperion/Runergy	HY-DH108P8-XXX(Y)	
JA Solar	JAM60S09-XXX/PR	JAM72S10-XXX/PR
	JAM60S10-XXX/MR	JAM72S12-XXX/PR
	JAM60S10-XXX/PR	JAM60S17-XXX/MR
	JAM60S12-XXX/PR	JAM54S30-XXX/MR
	JAM72S09-XXX/PR	JAM54S31-XXX/MR
	JAM72S10-XXX/MR	JAM72D30-XXX/MB
Jinko Solar	JKMXXXM-60	JKMXXXP-72-V
	JKMXXXM-60L	JKMXXXPP-72
	JKMXXXM-60HL	JKMXXXPP-72-V
	JKMXXXM-60HBL	JKMSXXXP-72
	JKMXXXP-60	JKMXXXM-72HL-V
	JKMXXXP-60-J4	JKMXXXM-72HL-TV
	JKMXXXP-60-V	JKMXXXM-72HBL
	JKMXXXP-60B-J4	JKMXXXM-6TL3-B
	JKMXXXPP-60	JKMXXXM-6RL3-B
	JKMXXXPP-60-V	JKMXXXM-7RL3-V
	JKMXXXM-72	JKMXXXM-7RL3-TV
	JKMXXXM-72L-V	JKMXXXM-72HL4-V
JKMXXXP-72	JKMXXXM-72HL4-TV	
LG	LGXXXN1C-A5	LGXXXA1C-V5
	LGXXXN1K-A5	LGXXXM1C-L5
	LGXXXQ1C-A5	LGXXXM1K-L5
	LGXXXQ1K-A5	LGXXXN1C-N5
	LGXXXS1C-A5	LGXXXN1K-L5
	LGXXXN2C-B3	LGXXXN1K-A6
	LGXXXN2W-B3	LGXXXN1C-A6

Manufacturer	Model	
	LGXXXN1C-G4	LGXXXN1W-A6
	LGXXXN1K-G4	LGXXXQ1C-A6
	LGXXXS1C-G4	LGXXXQ1K-A6
<p>APPROVED</p>	LGXXXN2C-G4	LGXXXM1K-A6
<p>Montgomery County</p>	LGXXXN2K-G4	LGXXXM1C-A6
<p>Historic Preservation Commission</p>	LGXXXN2W-G4	LGXXXA1C-A6
	LGXXXS2C-G4	LGXXXQAC-A6
	LGXXXS2W-G4	LGXXXQAK-A6
	LGXXXN1C-V5	LGXXXN1K-B6
	LGXXXN1W-V5	LGXXXN2W-E6
	LGXXXN2T-V5	LGXXXN2T-E6
	LGXXXN2T-J5	LGXXXN1K-E6
	LGXXXN1T-V5	LGXXXN3K-V6
	LR6-60-XXXM	LR4-60HPB-XXXM
<p>REVIEWED</p>	LR6-60BK-XXXM	LR4-60HIB-XXXM
<p>By Chris Berger at 11:27 am, Dec 11, 2023</p>	LR6-60HV-XXXM	LR4-60HPH-XXXM
	LR6-60PB-XXXM	LR4-60HIH-XXXM
<p>Longi</p>	LR6-60PE-XXXM	LR6-60HIH-XXXM
	LR6-60PH-XXXM	LR6-60HIB-XXXM
	LR6-60HPB-XXXM	LR4-72HPH-XXXM
	LR6-60HPH-XXXM	
<p>Meyer Burger</p>	Meyer Burger Black*	Meyer Burger White*
<p>mSolar</p>	TXI6-XXX120BB	
	MSEXXS05T	MSEXXSQ4S
	MSEXXS05K	MSEXXS8K
	MSEXXSQ5T	MSEXXS8T
	MSEXXSQ5K	MSEXXS9S
<p>Mission Solar</p>	MSEXXM4J	MSE60AXXX
	MSEXXM6J	MSEXXS5K
	MSEXXS06W	MSEXXS5T
	MSEXXS04J	MSEXXS6S
	MSEXXS06J	MSEXXS6W
	MSEXXSQ6S	MSEXXS5R
	USNEA-XXXM3-60	USNEA-XXXM3-72
<p>Next Energy Alliance</p>	USNEA-XXXM3B-60	USNEA-XXXM3B-72
	VBHNXXXKA03	VBHXXXRA18N
	VBHNXXXKA04	VBHXXXRA03K
<p>Panasonic</p>	VBHNXXXSA17	EVPVXXX(K)
	VBHNXXXSA18	EVPVXXXH
	VBHN325SA17E	EVPVXXXPK
	PSXXXM-20/U	PSxxxM8GF-18/VH
<p>Phono Solar</p>	PSXXXMH-20/U	PSxxxM8GFH-18/VH
	PSxxxM8GF-24/TH	PSxxxM6-24/TH
	PSxxxM8GFH-24/TH	

Manufacturer	Model	
<div style="border: 1px solid black; padding: 5px;"> <p style="text-align: center;">APPROVED</p> <p style="text-align: center;">Montgomery County Historic Preservation Commission</p>  </div>	RECXXTP2	RECXXTP2SM 72 BLK2
	RECXXTP2-BLK	RECXXAA
	RECXXNP	RECXXTP3M
	RECXXTP2M	RECXXTP4
	RECXXTP2M 72	RECXXAA Pure
	RECXXTP2M 72 BLK	RECXXAA Pure-R
	RECXXTP2M 72 BLK2	RECXXNP2
	RECXXTP2SM 72	RECXXNP3
	RECXXTP2SM 72 BLK	
	SEG-400-BMB-HV	SEG-xxx-BMD-HV
SEG-400-BMB-TB	SEG-xxx-BMD-TB	
<div style="border: 1px solid black; padding: 5px;"> <p>REVIEWED</p> <p>By Chris Berger at 11:27 am, Dec 11, 2023</p> </div>	SLAXX-M	SILXXNT
	SLAXX-P	SILXXHL
	SSAXX-M	SILXXBK
	XX-P	SILXXNX
	SILXXBL	SILXXNU
	SILXXML	SILXXHC
	SILXXNL	SILXXHN
	SLGXX-M	SILXXBG
	SLGXX-P	SIL-xxxHC+
	SSGXX-M	SIL-xxxHM
SSGXX-P		
Solaria	Solaria PowerXT-XXXR-PX	Solaria PowerXT-XXXR-PM
	Solaria PowerXT-XXXR-BX	Solaria PowerXT-XXXR-PM-AC
	Solaria PowerXT-XXXR-AC	
Sunpower	SPR-AXXX-G-AC	SPR-MXXX-H-AC
	SPR-AXXX	SPR-MXXX
	SPR-AXXX-BLK-G-AC	SPR-MXXX-BLK-H-AC
	SPR-AXXX-BLK	SPR-MXXX-BLK
SunSpark	SST-XXXM3-60	SST-XXXM3-72
	SST-XXXM3B-60	SST-XXXM3B-72
Talesun	TP660M-XXX	TP672M-XXX
	TP660P-XXX	TP672P-XXX
Trina	TSM-XXXDD05(II)	TSMXXXDD05H.05(II)
	TSM-XXXDD05A.05(II)	TSM-XXXDD06M.05(II)
	TSM-XXXDD05A.08(II)	TSM-XXXDE15H(II)
	TSM-XXXDD05A.082(II)	TSM-XXXDE15M(II)
	TSM-XXXPA05	TSMXXXDE06X.05(II)
	TSM-XXXPA05.05	TSMXXXDE09.05
	TSM-XXXPA05.08	TSM-XXXDE15V(II)
	TSM-XXXPD05	TSM-XXXDEG15VC.20(II)
	TSM-XXXPD05.002	TSM-XXXDEG18MC.20(II)
TSM-XXXPD05.05	TSM-XXXDEG19C.20	

Manufacturer	Model	
Trina	TSM-XXXPD05.05S	TSM-XXXDEG21C.20
	TSM-XXXPD05.08	TSM-XXXDE09C.05
	TSM-XXXPD05.082	TSM-XXXDE09C.07
	TSM-XXXPD05.08D	TSM-xxxNE09RC.05
	TSM-XXXPD05.08S	
Vikram Solar	SOMERA VSMHBB.60.XXX.05	PREXOS VSMDHT.60.XXX.05
	SOMERA VSMH.72.XXX.05	PREXOS VSMDHT.72.XXX.05
VSUN	VSUNXXX-144BMH-DG	VSUNXXX-108BMH
	VSUNXXX-120BMH	
ZNShine	ZXM6-60-XXX/M	ZXM6-NH144-XXXM
	ZXM6-NH120-XXXM	ZXM7-SH108-XXXM

APPROVED


Montgomery County
Historic Preservation Commission



REVIEWED
By Chris Berger at 11:27 am, Dec 11, 2023

SnapNrack TopSpeed™ has been tested with the following Module Level Power Electronic (MLPE) devices:

SnapNrack TopSpeed™ mounting systems has been tested with the following UL/NRTL Listed Module Level Power Electronic (MLPE) Devices. The back plates of the MLPEs have been evaluated for bonding to TopSpeed™ through the SnapNrack MLPE Frame Attachment Kit, model 242-02151.

MLPE Manufacturer	Model	
AP Smart	RSD-S-PLC	
<div style="border: 2px solid black; padding: 10px;"> <p style="text-align: center;">APPROVED</p> <p style="text-align: center;">Montgomery County Historic Preservation Commission</p>  </div>	DG-006-F001201x	DG-006-F001401x
	GPI00010105	
	C250	IQ7PLUS-72-2-US
	M215	IQ7PLUS-72-B-US
	M250	IQ8-60
	IQ6-60-2-US	IQ8PLUS-72
	IQ6PLUS-72-2-US	IQ8A-72
	IQ7-60-2-US	IQ8H-208-72
	IQ7-60-B-US	IQ8H-240-72
	Generec	S2502
<div style="border: 1px solid black; padding: 5px;"> <p>REVIEWED Technologies</p> <p>By Chris Berger at 11:27 am, Dec 11, 2023</p> </div>	Solis-RSD-1G	
	Solis-MLRSD-R1-1G	Solis-MLRSD-R2-1G
	P320-5NC4ARS	P320-5NC4ARS
	P370-5NC4AFS	P400-5NC4AFS
	P320	P340
	P370	P400
	P401	P405
	P485	P505
	P730	P800p
	P850	P860
	P950	P1100
	P1101	S440
	S500	
SMA	RSB-2S-US-10	
Tigo	TS4-R-F	TS4-R-M
	TS4-R-O	TS4-R-S
	TS4-R-M-DUO	TS4-R-O-DUO
	TS4-R-S-DUO	TS4-A-F
	TS4-A-2F	TS4-A-O
	TS4-A-S	

APPROVED
Montgomery County
Historic Preservation Commission



Single Phase Inverter with HD-Wave Technology

for North America

REVIEWED
By Chris Berger at 11:27 am, Dec 11, 2023

12-25
YEAR
WARRANTY



INVERTERS

Optimized installation with HD-Wave technology

- Specifically designed to work with power optimizers
- Record-breaking efficiency
- Fixed voltage inverter for longer strings
- Integrated arc fault protection and rapid shutdown for NEC 2014 and 2017, per article 690.11 and 690.12
- UL1741 SA certified, for CPUC Rule 21 grid compliance
- Extremely small
- Built-in module-level monitoring
- Outdoor and indoor installation
- Optional: Revenue grade data, ANSI C12.20 Class 0.5 (0.5% accuracy)

solaredge.com



Single Phase Inverter with HD-Wave Technology for North America

SE3000H-US / SE3800H-US / SE5000H-US / SE6000H-US /
SE7600H-US / SE10000H-US / SE11400H-US

	SE3000H-US	SE3800H-US	SE5000H-US	SE6000H-US	SE7600H-US	SE10000H-US	SE11400H-US		
OUTPUT									
Rated AC Power Output	3000	3800 @ 240V 3300 @ 208V	5000	6000 @ 240V 5000 @ 208V	7600	10000	11400 @ 240V 10000 @ 208V	VA	
Maximum AC Power Output	3000	3800 @ 240V 3300 @ 208V	5000	6000 @ 240V 5000 @ 208V	7600	10000	11400 @ 240V 10000 @ 208V	VA	
AC Output Voltage Min.-Nom.-Max. (211 - 240 - 264)	✓	✓	✓	✓	✓	✓	✓	Vac	
AC Output Voltage Min.-Nom.-Max. (183 - 208 - 229)	-	✓	-	✓	-	-	✓	Vac	
AC Frequency (Nominal)	59.3 - 60 - 60.5 ^①							Hz	
Maximum Continuous Output Current @240V	12.5	16	21	25	32	42	47.5	A	
Maximum Continuous Output Current @208V	-	16	-	24	-	-	48.5	A	
GFDI Threshold	1							A	
Utility Monitoring, Islanding Protection, Country Configurable Thresholds	Yes								
INPUT									
Maximum DC Power @240V	4650	5900	7750	9300	11800	15500	17650	W	
Maximum DC Power @208V	-	5100	-	7750	-	-	15500	W	
Transformer-less, Ungrounded	Yes								
Maximum Input Voltage	480							Vdc	
Nominal DC Input Voltage	380				400			Vdc	
Maximum Input Current @240V ^②	8.5	10.5	13.5	16.5	20	27	30.5	Adc	
Maximum Input Current @208V ^②	-	9	-	13.5	-	-	27	Adc	
Max. Input Short Circuit Current	45							Adc	
Reverse-Polarity Protection	Yes								
Ground-Fault Isolation Detection	600ka Sensitivity								
Maximum Inverter Efficiency	99	99.2						%	
CEC Weighted Efficiency	99						99 @ 240V 98.5 @ 208V	%	
Nighttime Power Consumption	< 2.5							W	
ADDITIONAL FEATURES									
Supported Communication Interfaces	RS485, Ethernet, ZigBee (optional), Cellular (optional)								
Revenue Grade Data, ANSI C12.20	Optional ^③								
Rapid Shutdown - NEC 2014 and 2017 690.12	Automatic Rapid Shutdown upon AC Grid Disconnect								
STANDARD COMPLIANCE									
Safety	UL1741, UL1741 SA, UL1699B, CSA C22.2, Canadian AFCI according to T.I.L. M-07								
Grid Connection Standards	IEEE1547, Rule 21, Rule 14 (HI)								
Emissions	FCC Part 15 Class B								
INSTALLATION SPECIFICATIONS									
AC Output Conduit Size / AWG Range	3/4" minimum / 14-6 AWG				3/4" minimum /14-4 AWG				
DC Input Conduit Size / # of Strings / AWG Range	3/4" minimum / 1-2 strings / 14-6 AWG				3/4" minimum / 1-3 strings / 14-6 AWG				
Dimensions with Safety Switch (HxWxD)	17.7 x 14.6 x 6.8 / 450 x 370 x 174				21.3 x 14.6 x 7.3 / 540 x 370 x 185				in / mm
Weight with Safety Switch	22 / 10	25.1 / 11.4	26.2 / 11.9	38.8 / 17.6				lb / kg	
Noise	< 25				<50			dBA	
Cooling	Natural Convection								
Operating Temperature Range	-40 to +140 / -25 to +60 ^④ (-40°F / -40°C option) ^⑤							°F / °C	
Protection Rating	NEMA 4X (Inverter with Safety Switch)								

^① For other regional settings please contact SolarEdge support
^② A higher current source may be used; the inverter will limit its input current to the values stated
^③ Revenue grade inverter P/N: SExxxxH-US000NNC2
^④ For power de-rating information refer to: <https://www.solaredge.com/sites/default/files/se-temperature-derating-note-na.pdf>
^⑤ -40 version P/N: SExxxxH-US000NNU4

Power Optimizer

For Residential Installations

S440 / S500 / S500B / S650B



REVIEWED

By Chris Berger at 11:27 am, Dec 11, 2023

POWER OPTIMIZER

Enabling PV power optimization at the module level

- Specifically designed to work with SolarEdge residential inverters
- Mitigates all types of module mismatch loss, from manufacturing tolerance to partial shading
- Detects abnormal PV connector behavior, preventing potential safety issues*
- Faster installations with simplified cable management and easy assembly using a single bolt
- Module-level voltage shutdown for installer and firefighter safety
- Flexible system design for maximum space utilization
- Superior efficiency (99.5%)
- Compatible with bifacial PV modules

* Functionality subject to inverter model and firmware version

Power Optimizer

For Residential Installations

S440 / S500 / S500B / S650B

APPROVED

Montgomery County
Historic Preservation Commission




	S440	S500	S500B	UNIT
INPUT				
Rated Input DC Power ⁽¹⁾	440	500	500	W
Absolute Maximum Input Voltage (Voc)	60	125	85	Vdc
MPPT Operating Range	8 – 60	12.5 – 105	12.5 - 85	Vdc
Maximum Short Circuit Current (Isc) of Connected PV Module	14.5	15	15	Adc
Maximum Efficiency				%
Weighted Efficiency				%
Overtoltage Category				
OUTPUT DURING OPERATION				
Maximum Output Current		15		Adc
Maximum Output Voltage	60		80	Vdc
OUTPUT DURING STANDBY (POWER OPTIMIZER DISCONNECTED FROM INVERTER OR INVERTER OFF)				
Safety Output Voltage per Power Optimizer		1 ± 0.1		Vdc
STANDARD COMPLIANCE⁽²⁾				
EMC	FCC Part 15 Class B, IEC61000-6-2, IEC61000-6-3, CISPR11, EN-55011			
Safety	IEC62109-1 (class II safety), UL1741			
Material	UL94 V-0, UV Resistant			
RoHS	Yes			
Fire Safety	VDE-AR-E 2100-712:2018-12			
INSTALLATION SPECIFICATIONS				
Maximum Allowed System Voltage		1000		Vdc
Dimensions (W x L x H)	129 x 155 x 30		129 x 165 x 45	mm
Weight	720		790	gr
Input Connector	MC4 ⁽³⁾			
Input Wire Length	0.1			m
Output Connector	MC4			
Output Wire Length	(+) 2.3, (-) 0.10			m
Operating Temperature Range ⁽⁴⁾	-40 to +85			°C
Protection Rating	IP68			
Relative Humidity	0 – 100			%

REVIEWED
By Chris Berger at 11:27 am, Dec 11, 2023

(1) Rated power of the module at STC will not exceed the Power Optimizer Rated Input DC Power. Modules with up to +5% power tolerance are allowed.
 (2) For details about CE compliance, see Declaration of Conformity – CE.
 (3) For other connector types please contact SolarEdge.
 (4) Power de-rating is applied for ambient temperatures above +85°C for S440 and S500, and for ambient temperatures above +75°C for S500B. Refer to the Power Optimizers Temperature De-Rating Technical Note for details.

PV System Design Using a SolarEdge Inverter ⁽⁵⁾		SolarEdge Home Wave Inverter Single Phase	SolarEdge Home Short String Inverter Three Phase	Three Phase for 230/400V Grid	Three Phase for 277/480V Grid	
Minimum String Length (Power Optimizers)	S440, S500	8	9	16	18	
	S500B, S650B	6	8		14	
Maximum String Length (Power Optimizers)		25	20		50	
Maximum Continuous Power per String		5700	5625	11,250	12,750	W
Maximum Allowed Connected Power per String ⁽⁶⁾ (In multiple string designs, the maximum is permitted only when the difference in connected power between strings is 2,000W or less)		6800 ⁽⁷⁾	See ⁽⁶⁾	13,500	15,000	W
Parallel Strings of Different Lengths or Orientations				Yes		

(5) It is not allowed to mix S-series and P-series Power Optimizers in new installations in the same string.
 (6) If the inverter's rated AC power ≤ maximum continuous power per string, then the maximum connected power per string will be able to reach up to the inverters maximum input DC power. Refer to the Single String Design Guidelines application note.
 (7) For inverters with a rated AC power ≥ 7600W that are connected to at least two strings.



PLAN VIEW

N.T.S.

APPROVED
Montgomery County
Historic Preservation Commission



Site Design Conditions

Basic Wind Speed: (Risk Category II)	110 MPH	Max. Leg Axial Bearing:	3,650 lbs
Basic Wind Speed: (Risk Category I)	102 MPH	Max. Leg Uplift:	2,280 lbs
Exposure Category:	C	Max. Lateral Resistance:	1,625 lbs
Ground Snow Load:	30 PSF	Top Rail Max. Loading:	99.4 plf
Flat Roof Snow Load:	N/A	Helical Pile Depth:	60" Min
Site Contour:	<5 Degree Slope	Lateral Resistance Plate Size:	Not Req'd


All design work has been performed in accordance with the Maryland Building Performance Standards Regulations including, but not limited to, the 2018 International Building Code with the Department of Labor, Licensing and Regulation modifications (ref: COMAR 09.12.51).

Net design pressures were calculated in accordance with ASCE 7-16 section 27.3.2, "Open Buildings with Monoslope, Pitched, or Troughed Roofs". All load cases were evaluated in determining the limiting design conditions. The data table above provides the results for the limiting load case. Maximum leg reaction forces represent the highest load condition seen by any leg in the structure. All legs in the structure are designed to meet the maximum load conditions.

4Lx10C Sub-Array Design Conditions

Front Leg Height:	31¼"	Array Tilt Angle:	25 Degrees
Rear Leg Height:	67½"	Front Edge Ground Clearance:	24"
North-South Leg Spacing:	78"	Overall Array East-West Dim:	57'-11"
West Span Leg Spacing:	15'-3"	Number of Modules/Sub-Array:	40
East Span Leg Spacing:	15'-3"	Number of Sub-Arrays:	1
Quantity Center Spans:	1	Module Columns/Sub-Array:	10
Center Span Leg Spacing:	15'-6"	Number of Module Rows:	4
East & West Overhang:	5'-0"	Module Orientation:	Landscape
Overall Beam Length:	56'-0"	Module Column Spacing:	¾"
Horizontal Beam Material:	5"x4"x½" HSS	Module Row Spacing:	¼"
Top Rail Material:	SF Rails	Module Model:	LR 4-60HPB-355M
Qty Rails per Panel:	2	Module Size:	40.87" x 69.09"
Top Rail Length:	171"	Individual Module Rating:	355 watts
Top Rail Center Span:	86"	Sub Array Power Rating:	14.20 kw
Top Rail Overhangs:	42½"	Total Power Rating:	14.20 kw

REVIEWED
By Chris Berger at 11:27 am, Dec 11, 2023



ISOMETRIC VIEW

N.T.S.

James C Douglas
Digitally signed by James C Douglas
DN: c=US, o=New York
dnQualifier=A01410C00001863CD5
41CS0004A600, cn=James C Douglas
Date: 2023.10.10 17:24:22 -0400




Professional Certification. I hereby certify that these documents were prepared or approved by me and that I am a duly licensed professional engineer under the laws of the State of Maryland, License No. 40027, Expiration Date: 3/15/25.

SHEET 1 OF 3			
DATE	REVISION	DRAWN BY:	REVIEW BY:
10/06/2023	ORIGINAL	JB	JD

SOLAR ENERGY WORLD
-PROJECT-
KINGSLEY, THEODORE RESIDENCE
14401 PARTNERSHIP ROAD
POOLESVILLE, MD 20837


Solar Foundations USA
1142 River Road, New Castle, DE 19720 Ph: (855) 738-7200 Fax: (866) 644-5665

S-1



SIDE ELEVATION


N.T.S.



REFER TO DWG SHEET 1 FOR EAST-WEST PILE SPANS AND FRONT AND REAR PILE HEIGHTS


PILE SPACING ELEVATION

N.T.S.




UPPER CAP DETAIL

N.T.S.



LOWER CAP DETAIL

N.T.S.



HELICAL PILE DETAIL

N.T.S.

APPROVED
Montgomery County
Historic Preservation Commission

REVIEWED
By Chris Berger at 11:27 am, Dec 11, 2023

James C Douglas
Digitally signed by James C Douglas
DN: c=US, o=New York,
dnQualifier=A01410C000001863CD5
41C50004A600, cn=James C Douglas
Date: 2023.10.10 17:23:50 -0400



Professional Certification. I hereby certify that these documents were prepared or approved by me and that I am a duly licensed professional engineer under the laws of the State of Maryland, License No. 40027, Expiration Date: 3/15/25.

SHEET 2 OF 3

DATE	REVISION	DRAWN BY:	REVIEW BY:
10/06/2023	ORIGINAL	JB	JD


SOLAR ENERGY WORLD

-PROJECT-
KINGSLEY, THEODORE RESIDENCE
14401 PARTNERSHIP ROAD
POOLESVILLE, MD 20837

Solar Foundations USA

1142 River Road, New Castle, DE 19720 Ph: (855) 738-7200 Fax: (866) 644-5665

S-2



HELICAL PILE DETAIL
N.T.S.

SPECIFICATION REQUIREMENTS:

THE FOLLOWING MATERIAL SPECIFICATION REQUIREMENTS PERTAIN TO THE FABRICATION OF THE SOLAR FOUNDATIONS USA GROUND MOUNT SOLAR SUPPORT STRUCTURE AS INDICATED ON THESE DRAWINGS.

1. SOLAR FOUNDATION ALUMINUM RAILS SHALL CONFORM TO ASTM B221.
2. STRUCTURAL STEEL TUBING SHALL BE ASTM A500 HIGH YIELD (60 KSI).
3. STEEL PIPE FOR PILES SHALL CONFORM TO ASTM A500 GRADE C.
4. STEEL PILE EXTENSIONS SHALL BE ASTM A53 GRADE B.
5. STEEL PIPE FOR DIAGONAL BRACING SHALL BE ASTM A53 GRADE A.
6. FABRICATED STEEL PLATE FOR COLUMN CAP ASSEMBLIES, BRACING CLAMPS, ETC. SHALL BE ASTM A36 OR A1011.
7. STEEL BOLTS FOR CAP FASTENERS SHALL CONFORM TO SAE J429 GRADE 5. ALL OTHER BOLTS SHALL CONFORM TO SAE J429 GRADE 5 OR BETTER.
8. STEEL U-BOLTS SHALL CONFORM TO ASTM 1018.
9. USS FLAT STEEL WASHERS SHALL CONFORM TO ASTM F844 AND NUTS FOR STEEL CONNECTIONS SHALL CONFORM TO ASTM A563 GRADE A.
10. ALL FIELD WELDING SHALL CONFORM TO AWS D1.1/D1.1M -STRUCTURAL WELDING CODE REQUIREMENTS.
11. ALL STEEL SHALL BE HOT-DIP GALVANIZED PER ASTM A123 OR A153 AFTER ALL FABRICATION HAS BEEN COMPLETED.

INSTALLATION REQUIREMENTS:


1. THE MINIMUM AVERAGE INSTALLATION TORQUE REQUIRED TO OBTAIN THE REQUIRED INDICATED CAPACITIES AND THE MINIMUM INSTALLATION DEPTH SHOWN ON THE PLANS SHALL BE SATISFIED PRIOR TO TERMINATION OF THE INSTALLATION. THE INSTALLATION TORQUE SHALL BE AN AVERAGE OF THE INSTALLATION TORQUES INDICATED DURING THE LAST 1 FOOT OF INSTALLATION.
2. THE TORSIONAL STRENGTH RATING OF THE TORQUE ANCHOR SHALL NOT BE EXCEEDED DURING THE INSTALLATION. IF THE TORSIONAL STRENGTH LIMIT OF THE ANCHOR HAS BEEN REACHED, BUT THE ANCHOR HAS NOT REACHED THE TARGET DEPTH, PERFORM THE FOLLOWING:
 - 2.1. IF THE TORSIONAL STRENGTH LIMIT IS ACHIEVED PRIOR TO REACHING THE TARGET DEPTH, THE INSTALLATION MAY BE ACCEPTABLE IF REVIEWED AND APPROVED BY THE ENGINEER.
 - 2.2. THE INSTALLER MAY REMOVE THE TORQUE ANCHOR AND INSTALL A NEW ONE WITH SMALLER DIAMETER HELICAL PLATE.
 - 2.3. IF USING A CONTINUOUS FLIGHT PILE, PRE-DRILL THE PILE LOCATION WITH A 3-1/2" ROCK AUGER OR 3-5/8" ROCK DRILL AS NEEDED.
3. IF THE TARGET DEPTH IS ACHIEVED, BUT THE TORSIONAL REQUIREMENT HAS NOT BEEN MET THE INSTALLER MAY DO ONE OF THE FOLLOWING:
 - 3.1. INSTALL THE TORQUE ANCHOR DEEPER TO OBTAIN THE REQUIRED CAPACITY
 - 3.2. REMOVE THE TORQUE ANCHOR AND INSTALL A NEW ONE WITH A LARGER DIAMETER HELICAL PLATE OR ONE WITH MULTIPLE HELICAL PLATES.
 - 3.3. REDUCE THE LOAD CAPACITY ON THE INDIVIDUAL TORQUE ANCHOR BY PROVIDING ADDITIONAL TORQUE ANCHORS AT A REDUCED SPACING.

APPROVED
Montgomery County
Historic Preservation Commission



REVIEWED
By Chris Berger at 11:27 am, Dec 11, 2023

James C Douglas
Digitally signed by James C Douglas
DN: cn=US, o=New York, dnQualifier=+01410C00001863C, DS41CS0004A600, cn=James C Douglas
Date: 2023.10.10 17:23:13 -0400



Professional Certification. I hereby certify that these documents were prepared or approved by me and that I am a duly licensed professional engineer under the laws of the State of Maryland, License No. 40027, Expiration Date: 3/15/25.

SHEET 3 OF 3

DATE	REVISION	DRAWN BY:	REVIEW BY:
10/06/2023	ORIGINAL	JB	JD

SOLAR ENERGY WORLD

-PROJECT-
KINGSLEY, THEODORE RESIDENCE
14401 PARTNERSHIP ROAD
POOLESVILLE, MD 20837

Solar Foundations USA

1142 River Road, New Castle, DE 19720 Ph: (855) 738-7200 Fax: (866) 644-5665

S-3

City of Takoma Park

Housing and Community Development Department

Main Office 301-891-7119
Fax 301-270-4568
www.takomaparkmd.gov



REVIEWED

venue
Takoma Park, MD 20912

By Chris Berger at 11:27 am, Dec 11, 2023

MUNICIPALITY LETTER

December 01, 2023

APPROVED

Montgomery County

Historic Preservation Commission

To: Ryan Doyle
7317 Willow Avenue
permitting@solarenergyworld.com

410-579-2009

To: Department of Permitting Services
2425 Reedie Drive, 7th floor
Wheaton, Maryland 20902

From: Planning and Development Services Division

THIS IS NOT A PERMIT – For Informational Purposes Only

VALID FOR ONE YEAR FROM DATE OF ISSUE

The property owner is responsible for obtaining all required permits from Montgomery County and the City of Takoma Park. If this property is in the **Takoma Park Historic District**, it is subject to Montgomery County Historic Preservation requirements.

Representative Name: Ryan Doyle

permitting@solarenergyworld.com 410-579-5172

Location of Project: 7317 Willow Avenue Takoma Park MD 20912

Proposed Scope of Work: Install (17) roof mounted solar panels, 6.20 kW

The purpose of this municipality letter is to inform you that the City of Takoma Park has regulations and city permit requirements that may apply to your project. This municipality letter serves as notification that, in addition to all Montgomery County requirements, you are required to comply with all City permitting requirements, including:

- Tree Impact Assessment/Tree Protection Plan
- Stormwater management
- City Right of Way

Failure to comply with these requirements could result in the issuance of a Stop Work Order and other administrative actions within the provisions of the law. Details of Takoma Park's permit requirements are attached on page 2.

The issuance of this letter does not indicate approval of the project nor does it authorize the property owner to proceed with the project. The City retains the right to review and comment on project plans during the Montgomery County review process.

City Of Takoma Park

The City of Takoma Park permits for the following issues:

Tree Impact Assessment/Tree Protection Plan/Tree Removal Application:

Construction activities that occur within 50 feet of any urban forest tree (7 and 5/8" in trunk diameter or greater), located on the project property or on an adjacent property, may require a Tree Impact Assessment and possibly a Tree Protection Plan Permit. Make sure to submit a request for a Tree Impact Assessment and schedule a site visit with the City's Urban Forest Manager if any urban forest tree is in the vicinity of proposed construction activities. See the Tree Permits section of the City website for the specific conditions in which a Tree Impact Assessment is required. Depending on the Urban Forest Manager's conclusion following the Tree Impact Assessment, you may need to prepare a full Tree Protection Plan and apply for a Tree Protection Plan Permit as well. Separately, the removal of any urban forest tree will require a Tree Removal Permit application. The tree ordinance is detailed in the City Code, section 12.12. For permit information check: <https://takomaparkmd.gov/services/permits/tree-permits>. The City's Urban Forest Manager can be reached at 301-891-7612 or urbanforestmanager@takomaparkmd.gov.

Stormwater Management:

If you plan to develop or redevelop property, you may be required to provide appropriate stormwater management measures to control or manage runoff, as detailed in City Code section 16.04. All commercial or institutional development in the city must apply for a Stormwater Management Permit regardless of the size of the land disturbance. Additions or modifications to existing detached single-family residential properties do not require a Stormwater Management permit if the project does not disturb more than 5,000 square feet of land area. For more information on visit: <https://takomaparkmd.gov/government/public-works/stormwater-management-program/>. The City Engineer should be contacted to determine if a City permit is required. The City Engineer can be reached at 301-891-7620.

City Right of Way:

- To place a **construction dumpster or storage container** temporarily on a City right of way (usually an adjacent road), you will need to obtain a permit. A permit is not required if the dumpster is placed in a privately-owned driveway or parking lot.
- If you plan to install a new **driveway apron**, or enlarge or replace an existing driveway apron, you need a Driveway Apron Permit.
- If you plan to construct a **fence** in the City right of way, you need to request a Fence Agreement. If approved, the Agreement will be recorded in the Land Records of Montgomery County.

For more information and applications for City permits, see: <https://takomaparkmd.gov/services/permits/> or contact the Department of Public Works at 301-891-7633.

Failure to comply with the City's permitting requirements could result in the issuance of a Stop Work Order and other administrative actions within the provisions of the law.

eSigned via SeamlessDocs.com
Ryan Doyle
Key: 38bf2056622713c0b979ea7ee94776a

Ryan Doyle

eSigned via SeamlessDocs.com
Takoma Park Planning Division
Key: 19fe84f123e98a3ff45762

REVIEWED

By Chris Berger at 11:27 am, Dec 11, 2023

APPROVED
Montgomery County
Historic Preservation Commission

